

IM 1003: Programming Design

Operator Overloading

Ling-Chieh Kung

Department of Information Management
National Taiwan University

April 21, 2014

Outline

- **Motivations and basic concepts**
- Overloading comparison and indexing operators
- Overloading assignment and self-assignment operators
- Overloading addition operators

Recall our MyVector class

```
class MyVector
{
private:
    int n;
    double* m;
public:
    MyVector() : n(0), m(NULL) { };
    MyVector(int n, double m[]);
    MyVector(const MyVector& v);
    ~MyVector() { delete [] m; }
    void print() const;
};
```

```
MyVector::MyVector(int n, double m[])
{
    this->n = n;
    this->m = new double[n];
    for(int i = 0; i < n; i++)
        this->m[i] = m[i];
}

MyVector::MyVector(const MyVector& v)
{
    this->n = v.n;
    this->m = new double[n];
    for(int i = 0; i < n; i++)
        this->m[i] = v.m[i];
}

void MyVector::print() const
{
    cout << "(";
    for(int i = 0; i < n - 1; i++)
        cout << m[i] << ", ";
    cout << m[n-1] << ")\\n";
}
```

Comparing MyVector objects

- When we have many vectors, we may need to **compare** them.
- For vectors u and v :
 - $u = v$ if their dimensions are equal and $u_i = v_i$ for all i .
 - $u < v$ if their dimensions are equal and $u_i < v_i$ for all i .
 - $u \leq v$ if their dimensions are equal and $u_i \leq v_i$ for all i .
- How to add **member functions** that do comparisons?
 - Naturally, they should be **instance** rather than static functions.

Member function `isEqual()`

```
class MyVector
{
private:
    int n;
    double* m;
public:
    MyVector() : n(0), m(NULL) { };
    MyVector(int n, double m[]);
    MyVector(const MyVector& v);
    ~MyVector() { delete [] m; }
    void print() const;
    bool isEqual(const MyVector& v) const;
};
```

```
bool MyVector::isEqual(const MyVector& v) const
{
    if(this->n != v.n)
        return false;
    else
    {
        for(int i = 0; i < n; i++)
        {
            if(this->m[i] != v.m[i])
                return false;
        }
    }
    return true;
}
```

Member function `isEqual()`

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);
    double d2[4] = {1, 2, 3, 4};
    const MyVector a2(4, d2);
    const MyVector a3(a1);

    if(a1.isEqual(a2))
        cout << "Y\n";
    else
        cout << "N\n"; // N

    if(a1.isEqual(a3))
        cout << "Y\n"; // Y
    else
        cout << "N\n";
    return 0;
}
```

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);

    double d2[4] = {1, 2, 3, 4};
    const MyVector a2(4, d2);
    const MyVector a3(a1);

    a1.isEqual(a2) ? cout << "Y\n" : cout << "N\n";
    a1.isEqual(a3) ? cout << "Y\n" : cout << "N\n";

    return 0;
}
```

- The ternary operator “`? :`” can be used to condense a program.

`isEqual ()` is fine, but ...

- Adding the instance function `isEqual ()` is fine.
 - But it is not intuitive.
 - If we can write `if (a1 == a2)`, it will be great!
- Of course we cannot:
 - The compiler does not know what to do to this statement.
 - We need to define `==` for `MyVector` just as we define member functions.
- In fact, `==` has been **overloaded** for different data types.
 - We may compare two **ints**, two **doubles**, one **int** and one **double**, etc.
 - We will now define how `==` should compare two **MyVectors**.
- This is **operator overloading**.

Operator overloading

- Most operators (if not all) have been overloaded in the C++ standard.
 - E.g., the division operator `/` has been overloaded.
 - Divisions between integers is just different from divisions fractional values!
- Overloading operators for self-defined classes are **not required**.
 - Each overloaded operator can be replaced by an instance function.
 - However, it often makes programs **clearer** and the class **easier to use**.
- Some **restrictions**:
 - Not all operators can be overloaded (see your textbook).
 - The number of operands for an operator cannot be modified.
 - New operators cannot be created.

Outline

- Motivations and basic concepts
- **Overloading comparison and indexing operators**
- Overloading assignment and self-assignment operators
- Overloading addition operators

Overloading an operator

- An operator is overloaded by “implementing a **special instance function**”.
 - It cannot be implemented as a static function.
- Let op be the operator to be overloaded, the “special instance function” is always named

`operatorop`

- The keyword **operator** is used for overloading operators.
- Let's overload `==` for **MyVector**.

Overloading ==

- Recall that we defined `isEqual()`:

```
class MyVector
{
private:
    int n;
    double* m;
public:
    MyVector() : n(0), m(NULL) { };
    MyVector(int n, double m[]);
    MyVector(const MyVector& v);
    ~MyVector() { delete [] m; }
    void print() const;
    bool isEqual(const MyVector& v) const;
};
```

```
bool MyVector::isEqual(const MyVector& v) const
{
    if(this->n != v.n)
        return false;
    else
    {
        for(int i = 0; i < n; i++)
        {
            if(this->m[i] != v.m[i])
                return false;
        }
    }
    return true;
}
```

Overloading ==

- To overload ==, simply do this:

```
class MyVector
{
private:
    int n;
    double* m;
public:
    MyVector() : n(0), m(NULL) { };
    MyVector(int n, double m[]);
    MyVector(const MyVector& v);
    ~MyVector() { delete [] m; }
    void print() const;
    bool operator==(const MyVector& v) const;
};
```

```
bool MyVector::operator==(const MyVector& v) const
{
    if(this->n != v.n)
        return false;
    else
    {
        for(int i = 0; i < n; i++)
        {
            if(this->m[i] != v.m[i])
                return false;
        }
    }
    return true;
}
```

- So easy!

Invoking overloaded operators

- We are indeed implementing instance functions with special names.
- Regarding **invoking** these instance functions:

```
int main() // without operator overloading
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);

    double d2[4] = {1, 2, 3, 4};
    const MyVector a2(4, d2);
    const MyVector a3(a1);

    a1.isEqual(a2) ? cout << "Y\n" : cout << "N\n";
    a1.isEqual(a3) ? cout << "Y\n" : cout << "N\n";

    return 0;
}
```

```
int main() // with operator overloading
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);

    double d2[4] = {1, 2, 3, 4};
    const MyVector a2(4, d2);
    const MyVector a3(a1);

    a1 = a2 ? cout << "Y\n" : cout << "N\n";
    a1 = a3 ? cout << "Y\n" : cout << "N\n";

    return 0;
}
```

Invoking overloaded operators

- Interestingly, we may also do:

```
int main() // with operator overloading
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);

    double d2[4] = {1, 2, 3, 4};
    const MyVector a2(4, d2);
    const MyVector a3(a1);

    a1.operator==(a2) ? cout << "Y\n" : cout << "N\n";
    a1.operator==(a3) ? cout << "Y\n" : cout << "N\n";

    return 0;
}
```

Overloading <

- Let's overload <:

```
class MyVector
{
private:
    int n;
    double* m;
public:
    MyVector() : n(0), m(NULL) { };
    MyVector(int n, double m[]);
    MyVector(const MyVector& v);
    ~MyVector() { delete [] m; }
    void print() const;
    bool operator==(const MyVector& v) const;
    bool operator<(const MyVector& v) const;
};
```

```
bool MyVector::operator<(const MyVector& v) const
{
    if(this->n != v.n)
        return false;
    else
    {
        for(int i = 0; i < n; i++)
        {
            if(this->m[i] >= v.m[i])
                return false;
        }
    }
    return true;
}
```

- So easy!

Overloading !=

- To overload !=, let's utilize the overloaded ==:

```
class MyVector
{
    // ...
    bool operator==(const MyVector& v) const;
    bool operator!=(const MyVector& v) const;
};
```

```
bool MyVector::operator!=(const MyVector& v) const
{
    if(*this == v)
        return false;
    else
        return true;
    // or return !(*this == v);
}
```

- How would you overload >=?

Parameters for overloaded operators

- The number of parameters is **restricted** for overloaded operators.
 - The **types of parameters** are not restricted.
 - The **return type** is not restricted.
 - **What is done** is not restricted.
- Always avoid unintuitive implementations!

```
class MyVector
{
    // ...
    bool operator==(const Vector& v) const;
    bool operator==(MyVector v) const;
    void operator==(int i) const
    {
        cout << "...\\n";
    } // no error but never do this!
    bool operator==(int i, int j); // error
};
```

Overloading the indexing operator

- Another natural operation that is common for vectors is indexing.
 - Given vector v , we want to know/modify the element v_i .
- For C++ arrays, we use the indexing operator `[]`.
- May we overload `[]` for **MyVector**? Yes!

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    const MyVector a1(5, d1);
    cout << a1[3] << endl; // endl is a new line object
    a1[1] = 4;

    return 0;
}
```

Overloading the indexing operator

- Let's overload []:

```
class MyVector
{
    // ...
    double operator[] (int i) const;
};
```

```
double MyVector::operator[] (int i) const
{
    if(i < 0 || i >= n)
        exit(1); // terminate the program!
                // required <cstdlib>
    return m[i];
}
```

- **exit(1)** terminates the program by sending 1 to the operating system.
- **return 0** in the main function terminates the program by sending 0.
- 0: Normal termination. Other numbers: different errors.

More are needed for []

- Compiling the program with the main function below results in an error!

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    MyVector a1(5, d1); // non-const
    cout << a1[3] << endl; // good
    a1[1] = 4; // error!

    return 0;
}
```

- Error: **a1[1]** is just a **literal**, not a variable.
 - A literal cannot be put at the LHS in an assignment operation!
 - Just like **3 = 5** results in an error.

Another overloaded []

- Let's overload [] into another version:

```
class MyVector
{
    // ...
    double operator[](int i) const;
    double& operator[](int i);
};
```

```
double MyVector::operator[](int i) const
{
    if(i < 0 || i >= n)
        exit(1);
    return m[i];
}
double& MyVector::operator[](int i)
{
    if(i < 0 || i >= n)
        exit(1);
    return m[i];
}
```

- The second implementation returns a **reference** of a member variable.
 - Modifying that reference modifies the variable.

Two different []

- Now the program runs successfully!

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    MyVector a1(5, d1);
    cout << a1[1] << endl; // 2
    a1[1] = 4; // good
    cout << a1[1] << endl; // 4

    return 0;
}
```

- There is one last question:
 - Which [] is invoked?

```
class MyVector
{
    // ...
    double operator[](int i) const;
    double& operator[](int i);
};
```

```
double MyVector::operator[](int i) const
{
    if(i < 0 || i >= n)
        exit(1);
    return m[i];
}

double& MyVector::operator[](int i)
{
    if(i < 0 || i >= n)
        exit(1);
    return m[i];
}
```

Invoking the two []

- The `const` after the function prototype is the key.

```
class MyVector
{
    // ...
    double operator[] (int i) const;
    double& operator[] (int i);
};
```

- If there are both a constant and a non-constant version:
 - A constant function is invoked by a constant object.
 - A non-constant function is invoked by a non-constant object.
- If there is only a non-constant instance function:
 - A constant object cannot invoke it.

Outline

- Motivations and basic concepts
- Overloading comparison and indexing operators
- **Overloading assignment and self-assignment operators**
- Overloading addition operators

Operations that modify the object

- Some operations do not modify the calling object.
 - E.g., comparisons and indexing.
- Some operations modify the calling object.
 - E.g., assignments and self-assignments.
- Let's overload the assignment operator = first.
- What do we expect?

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    double d2[4] = {1, 2, 3, 4};
    MyVector a1(5, d1);
    MyVector a2(4, d2);

    a2.print();
    a2 = a1; // assignment
    a2.print();

    return 0;
}
```

Default assignment operator

- In fact, the assignment operator has been overloaded!
 - The compiler adds a **default assignment operator** into each class.
 - It simply **copies each instance variable** to its corresponding one.
 - Just like the default copy constructor.
- What may be wrong when we run the main function with the default assignment operator?
 - Note the **destructor!**

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    double d2[4] = {1, 2, 3, 4};
    MyVector a1(5, d1);
    MyVector a2(4, d2);

    a2.print();
    a2 = a1; // dangerous!
    a2.print();

    return 0;
}
```

Overloading the assignment operator

- The assignment operator must be manually overloaded when there are pointers in a class.
 - Just like the copy constructor.
- Our first implementation:

```
class MyVector
{
    // ...
    void operator=(const MyVector& v);
};
```

- How about **a1 = a1**?

```
void MyVector::operator=(const MyVector& v)
{
    if(this->n != v.n)
    {
        delete [] this->m;
        this->n = v.n;
        this->m = new double[this->n];
    }
    for(int i = 0; i < n; i++)
        this->m[i] = v.m[i];
}
```

Overloading the assignment operator

- Our second implementation:

```
class MyVector
{
    // ...
    void operator=(const MyVector& v);
};
```

- How about `a1 = a2 = a3`?

```
void MyVector::operator=(const MyVector& v)
{
    if(this != &v)
    {
        if(this->n != v.n)
        {
            delete [] this->m;
            this->n = v.n;
            this->m = new double[this->n];
        }
        for(int i = 0; i < n; i++)
            this->m[i] = v.m[i];
    }
}
```

Overloading the assignment operator

- Our third implementation:

```
class MyVector
{
    // ...
    MyVector& operator=(const MyVector& v);
};
```

- To avoid $(a1 = a2) = a3$, we may return `const MyVector&`.

```
MyVector& MyVector::operator=(const MyVector& v)
{
    if(this != &v)
    {
        if(this->n != v.n)
        {
            delete [] this->m;
            this->n = v.n;
            this->m = new double[this->n];
        }
        for(int i = 0; i < n; i++)
            this->m[i] = v.m[i];
    }
    return *this;
}
```

Preventing assignments and copying

- In some cases, we **disallow** assignments between objects of a certain class.
 - To do so, overload the assignment operator as a **private** member.
- In some cases, we disallow creating an object by **copying** another object.
 - To do so, implement the copy constructor as a **private** member.
- The copy constructor, assignment operator, and destructor form a group.
 - If there is no pointer, **none** of them is needed.
 - If there is a pointer, **all** of them are needed.

Self-assignment operators

- For vectors, it is often to do arithmetic and assignments.
 - Given vectors u and v of the same dimension, the operation $u += v$ makes u_i become $u_i + v_i$ for all i .
- Let's overload `+=`:
 - Why returning `const MyVector&`?
- Returning `MyVector&` allows `(a1 += a3) [i]`.
- Returning `const MyVector&` disallows `(a1 += a3) = a2`.

```
class MyVector
{
    // ...
    const MyVector& operator+=(const MyVector& v);
};
const MyVector& MyVector::operator+=(const MyVector& v)
{
    if(this->n == v.n)
    {
        for(int i = 0; i < n; i++)
            this->m[i] += v.m[i];
    }
    return *this;
}
```

Outline

- Motivations and basic concepts
- Overloading comparison and indexing operators
- Overloading assignment and self-assignment operators
- **Overloading addition operators**

Arithmetic operators

- Overloading an arithmetic operator is not hard.
- Consider the addition operator `+` as an example.
 - Take `const MyVector&` as a parameter.
 - Add each pair of elements one by one.
 - Do not modify the calling object.
 - Return `const MyVector` to allow `a1 + a2 + a3` but disallow `(a1 + a2) = a3`.

Overloading the addition operator

- Let's try to do it.

```
class MyVector
{
    // ...
    const MyVector operator+(const MyVector& v) ;
};
const MyVector MyVector::operator+(const MyVector& v)
{
    MyVector sum(*this); // creating a local variable
    sum += v; // using the overloaded +=
    return sum;
}
```

- Why not returning `const MyVector&`?

Overloading the addition operator

- We may overload it for another parameter type:

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    MyVector a1(5, d1);
    MyVector a2(5, d1);

    a1 = a1 + a2; // good
    a1.print();
    a1 = a2 + 4.2; // good
    a1.print();

    return 0;
}
```

```
class MyVector
{
    // ...
    const MyVector operator+(const MyVector& v);
    const MyVector operator+(double d);
};

const MyVector MyVector::operator+(const MyVector& v)
{
    MyVector sum(*this); // creating a local variable
    sum += v; // using the overloaded +=
    return sum;
}

const MyVector MyVector::operator+(double d)
{
    MyVector sum(*this);
    for(int i = 0; i < n; i++)
        sum[i] += d;
    return sum;
}
```

Instance function vs. global function

- One last issue: addition is **commutative**, but the program below does not run!

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    MyVector a1(5, d1);

    a1 = 4.2 + a1; // bad!
    a1.print();

    return 0;
}
```

- We cannot let a double variable invoke our “instance function **operator+**”.
- We should overload **+** as a **global function**.

A global-function version

- To overload `+` as global functions, we need to handle the three combinations:

```
const MyVector operator+(const MyVector& v, double d)
{
    MyVector sum(v);
    for(int i = 0; i < v.n; i++) // What do we need for this?
        sum[i] += d; // pairwise addition
    return sum;
}
const MyVector operator+(double d, const MyVector& v)
{
    return v + d; // using the previous definition
}
const MyVector operator+(const MyVector& v1, const MyVector& v2)
{
    MyVector sum(v1);
    return sum += v2; // using the overloaded +=
}
```

A global-function version

- Now all kinds of addition may be performed:

```
int main()
{
    double d1[5] = {1, 2, 3, 4, 5};
    MyVector a1(5, d1);
    MyVector a3(a1);

    a3 = 3 + a1 + 4 + a3;
    a3.print();

    return 0;
}
```

- Each operator needs a separate consideration.